

# SPECIFICATION SHEET: WEATHERWOOD MAINTENANCE OIL TOPCOATS

W▲W  
WEATHERWOOD▲STAINS

## Architectural Wood Products

▲ VINTAGE WOOD, WITHOUT THE HUNDRED YEAR WAIT ▲



### MSRP WOOD STAIN PRICING:

- ▲ QUART @ \$79
- ▲ GALLON @ \$300

### MSRP MAINTENANCE OILS

- ▲ 1/2 PINT @ \$40
- ▲ QUART @ \$120

### MSRP EXTERIOR WATERPROOFER

- ▲ QUART @ \$32
- ▲ GALLON @ \$95

### MSRP VARNISH

- ▲ QUART @ \$40
- ▲ GALLON @ \$120

ORDERING INFO: ORDER ONLINE OR  
CALL PH. (801) 623-2609 | 9-5 EST

[WWW.WEATHERWOODSTAINS.COM](http://WWW.WEATHERWOODSTAINS.COM)

### WW MAINTENANCE OILS

WW Maintenance Oil topcoats are architectural quality specially formulated to accentuate the Weatherwood reactive, wood stains' colors. Maintenance Oils come in two colors, white and clear.

**WHITE:** Used to maintain the color of lightly colored stained woods or to lighten dark colored woods.

**CLEAR:** Used to darken and warm light colored wood. To hold the rustic look of dark colored woods.

WW Varnishes are:

- ▲ Architectural Quality
- ▲ Stain Resistant
- ▲ Oil-Based
- ▲ Commercial & Residential
- ▲ Moisturizes Wood

### USE:

For flooring, furniture, cabinetry, millwork, doors, wainscoting, paneling, etc. 1 Quart = 400 sq. ft.



### DIRECTIONS:

**PREP:** Apply as a topcoat WeatherwoodStains reactive wood stain. Allow stains are dry, sanding with 120-220 optional.

**APPLICATION:** Use cloth or brush to apply. Apply one very light coat of oil, using one brush/cloth to apply oil and a second clean cloth to buff product back off. Apply up to three coats based on look and desired protection.

**DRYING:** Maintenance Oil should cure 24-48 hours. Proper air flow and warm conditions aid dry time. Allow longer for damp/humid climates.

**CARE:** Apply maintenance oil yearly to keep the hard-wax look.

\* Optional step, allow maint. oil to cure full dry time. Apply an additional topcoat, like poly, lacquer, varnish. to seal in look.

